

## SLICKY STICKY®

## LOWER COSTS - BETTER RESULTS

Slicky Sticky<sup>®</sup> is a soil amendment that helps control soil erosion. It promotes water penetration into the soil, which reduces water run-off. It also flocculates suspended soil particles minimizing soil loss.

Slicky Sticky<sup>®</sup> makes any mulch slurry slippery which helps reduce or eliminate clogging. Also, more mulch can be used per tank load. More mulch per tank load increases productivity.

Slicky Sticky® helps capture more soil moisture which results in improved seed germination.

Slicky Sticky® reduces costs and improves productivity. Less erosion means fewer call backs. Fewer clogs means less down time. More mulch per tank load results in greater coverage per load.

Slicky Sticky® is environmentally safe, E.P.A. exempt, and totally biodegradable in 3 to 6 months.

Mixing Instructions: Use is 2-8 ounces per 100 gallons of slurry. Slowly add to the slurry during agitation. Allow to mix at least five minutes. NEVER 100 gallons of slurry. five minutes. NEVER MIX MORE THAN 8 OUNCES PER 100 GALLONS OF WATER.

APPLICATION RATES VARY FROM 3-20 POUNDS PER ACRE: Soil erosion is caused by flowing water. The volume and velocity of flowing water data. velocity of flowing water determines the severity. Steep slopes may not require more than about 3 pounds per acre of slicky. Slight slopes with a bind of the severity of the severity of the severity of the slopes with a bind of the severity. Sticky. Slight slopes with a high volume and high velocity of flowing water, running off from higher areas, may be impossible to control. It is not possible to a to control. It is not possible for Turfmaker Corp to guarantee the performance of any soil erosion product. 800-527-2304

TURFMAKER CORP

ROWLETT, TX 75088

SLICKYSTICKY.COM

972-463-2575